

Quantity/Type	1×CVBS 1×VGA（RGBHV） 1×DVI（ VESA / CEA-861） 1×HDMI VESA / CEA-861） 2×USB 2.0	
Composite Video	PAL / NTSC	
Video Amplitude/Impedance	1V (p_p) / 75Ω	
HDMI	PC（VESA Standard） / HDMI1.3（CEA-861）	≤1920x1280@60Hz
DVI	PC（VESA Standard） / DVI1.4（CEA-861）	≤1920x 1280@60Hz
VGA	VGA（RGBHV Standard）	≤1920×1080@60Hz
CVBS	Support PAL, PAL-M/N, NTSC, SECAM format	
USB	USB2.0 standard	≤1920 x 1080@60Hz
Input Terminal	CVBS：BNC VGA：15pin D_Sub（Female） DVI：24+1 DVI_D HDMI：HDMI Type A	
Output Signal		
Amount / Type	2x DVI 1x AUDIO	
DVI Format	1024×768@60 Hz 1280×720@60 Hz 1280×1024@60 Hz 1600×1200@60 Hz 1920×1080@60 Hz 1920×1200@60 Hz 1920×1280@60 Hz	
Customized Output Resolution	@60Hz： (2.65 million pixels) 4096*640@60 Hz 3840*720@60 Hz 2560*1080@60 Hz 1340*2018@60 Hz @30Hz： 530 (5.3 million pixels) 4096*640@30 Hz	

	3840*720@30 Hz 2560*1080@30Hz 1340*2018@30Hz
AUDIO Format	Stereo Output
Output Terminal	DVI OUT : 24+1 DVI_D AUDIO OUT : AUDIO
Control Port	RS232
Control& Update	USB-CTL
Input AC Power	230 V AC 50/60 Hz
Packing Size	535 x 35 x 145 mm (L x W x H)
Weight	2500 g
Power Consumption	22 W
Ambient Temperature	0-50 °C
Ambient Humidity	15-90%
Standard Accessory	1x Power Cable 1,2 m
	1x DVI Cable 0,5 m
	1x HDMI cable 1,5 m
	1 User Manual